

Overview

Models

HP FlexFabric 7904 Switch Chassis

JG682A

Key features

- Nonblocking and lossless Clos architecture
 - Large Layer 2 scaling with TRILL and HP IRF
 - Overlay technologies like VXLAN and NVGRE
 - Enhanced modularity with control and data plane separation
 - High 40GbE density across 3.84 Tb/s switch fabric
-

Product overview

HP FlexFabric 7900 Switch Series is the next generation compact modular data center core switch designed to support virtualized data centers and evolution needs of private and public clouds deployments.

The 7900 delivers unprecedented levels of performance, buffering, scale, and availability with high density 40GbE interfaces using only a fraction of the foot print used by traditional chassis.

Ready for software-defined networking (SDN) and VxLAN/NVGRE tunneling technologies, the switch supports full Layer 2 and 3 features.

Features and benefits

Product architecture

- **Modern scalable system architecture**
provides nonblocking, lossless Clos architecture with VOQs and large buffers with the flexibility and scalability for future growth
- **Distributed architecture with separation of data and control planes**
delivers enhanced fault tolerance and facilitates continuous operation and zero service disruption during planned or unplanned control-plane events
- **Advanced Comware modular operating system**
brings native high stability, independent process monitoring, and restart through the modular design and multiple processes of HP Comware v7 software; supports enhanced serviceability functions Performance
- **High-performance fully distributed architecture**
delivers up to 3.84 Tb/s switching capacity and 2.38 Bpps throughput with nonblocking wirespeed performance
- **High-density 40GbE interface connectivity**
offers up to 4 interface module slots to scale up to 48 40GbE ports
- **Distributed scalable fabric architecture**
integrated fabric and management modules to deliver more than 1 Tb per slot bandwidth

Data center optimized

- **Front-to-back airflow design**
accommodates deployment in data centers utilizing hot-cold aisles

Resiliency and high availability



Overview

- **Redundant/load-sharing fan assemblies, and power supplies**
increase total performance and power availability while providing hitless, stateful failover
- **Hot-swappable modules**
allows replacement of modules without any impact on other modules
- **Graceful restart**
allows routers to indicate to others their capability to maintain a routing table during a temporary shutdown, which significantly reduces convergence times upon recovery; supports OSPF, BGP, and IS-IS
- **Virtual Router Redundancy Protocol (VRRP)**
allows groups of two routers to dynamically back each other up to create highly available routed environments
- **Device Link Detection Protocol (DLDP)**
monitors link connectivity and shuts down ports at both ends if unidirectional traffic is detected, preventing loops in STP based networks
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP)**
supports up to 1024 trunk groups and up to 16 members per trunk; supports static or dynamic groups and a user-selectable hashing algorithm
- **Mid plane free chassis design**
delivers increased system reliability and optimal airflow as the chassis has no mid plane and line cards connect directly to the onboard fabric card
- **Ultrafast protocol convergence (subsecond) with standard-based failure detection—Bidirectional Forwarding Detection (BFD)**
enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS and VRRP

Layer 2 switching

- **VLAN**
supports up to 4,094 port-based or IEEE 802.1Q-based VLANs
- **Port mirroring**
duplicates port traffic (ingress and egress) to a local or remote monitoring port; supports four mirroring groups, with an unlimited number of ports per group
- **Port isolation**
increases security by isolating ports within a VLAN while still allowing them to communicate with other VLANs
- **Internet Group Management Protocol (IGMP) and Multicast**
Listener Discovery (MLD) protocol snooping controls and manages the flooding of multicast packets in a Layer 2 network
- **Spanning Tree Protocol (STP)**
supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

Layer 3 routing

- **Open shortest path first (OSPF)**
delivers faster convergence; uses this link-state routing Interior Gateway Protocol (IGP), which supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Intermediate system to intermediate system (IS-IS)**
uses a path vector Interior Gateway Protocol (IGP), which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Border Gateway Protocol 4 (BGP-4)**
delivers an implementation of the Exterior Gateway Protocol (EGP) utilizing path vectors; uses TCP for enhanced reliability for the route discovery process; reduces bandwidth consumption by advertising only incremental updates; supports extensive policies for increased flexibility; scales to very large networks
- **Equal-Cost Multipath (ECMP)**

Overview

enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth

- **Unicast Reverse Path Forwarding (uRPF)**
limits erroneous or malicious traffic in accordance with RFC 3074
- **Static IPv4 routing**
provides simple manually configured IPv4 routing
- **Routing Information Protocol (RIP)**
uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- **IP performance optimization**
provides a set of tools to improve the performance of IPv4 networks; includes directed broadcasts, customization of TCP parameters, support of ICMP error packets, and extensive display capabilities

Quality of Service (QoS)

- **IEEE 802.1p prioritization**
delivers data to devices based on the priority and type of traffic
- **Flexible classification**
creates traffic classes based on access control lists (ACLs), IEEE 802.1p precedence, IP, and DSCP or Type of Service (ToS) precedence; supports filter, redirect, mirror, remark, and logging
- **Bandwidth shaping**
 - Port-based rate limiting provides per-port ingress-/egress-enforced increased bandwidth
 - Classifier-based rate limiting uses an access control list (ACL) to enforce increased bandwidth for ingress traffic on each port
 - Reduced bandwidth provides per-port, per-queue egress-based reduced bandwidth
- **Broad QoS feature set**
provides support for Strict Priority Queuing (SP), Weighted Fair Queuing (WFQ), Weighted Deficit Round Robin (WDRR), SP+WDRR together, configurable buffers and Explicit Congestion Notification (ECN)
- **Traffic policing**
supports Committed Access Rate (CAR) and line rate

Layer 3 services

- **Address Resolution Protocol (ARP)**
determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper**
redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- **Dynamic Host Configuration Protocol (DHCP)**
simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

Management

- **Management interface control**
enables or disables each of the following interfaces depending on security preferences: console port, telnet port, or reset button
- **Industry-standard CLI with a hierarchical structure**
reduces training time and expenses, and increases productivity in multivendor installations
- **SNMPv1, v2, and v3**
provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption

Overview

- **sFlow** (RFC 3176)
provides scalable ASIC-based wirespeed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **Remote monitoring** (RMON)
uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **Debug and sampler utility**
supports ping and traceroute
- **Network Time Protocol** (NTP)
synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Network Quality Analyzer** (NQA)
analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays and file transfer rates; allows a network manager to determine overall network performance and to diagnose and locate network congestion points or failures
- **IEEE 802.1AB Link Layer Discovery Protocol** (LLDP)
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications

Connectivity

- **Jumbo frames**
allows high-performance backups and disaster-recovery systems with a maximum frame size of 12288 bytes
- **Loopback**
supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **Packet storm protection**
protects against unknown broadcast, unknown multicast, or unicast storms with user-defined thresholds
- **Flow control**
provides back pressure using standard IEEE 802.3x, reducing congestion in heavy traffic situations

Security

- **Access control list** (ACL)
used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can be set to operate on specific dates or times
- **Remote Authentication Dial-In User Service** (RADIUS)
eases switch security access administration by using a password authentication server
- **Secure shell** (SSHv2)
uses external servers to securely log in to a remote device; with authentication and encryption, it protects against IP spoofing and plain-text password interception; increases the security of Secure FTP (SFTP) transfers
- **DHCP snooping**
helps ensure that DHCP clients receive IP addresses from authorized DHCP servers and maintain a list of DHCP entries for trusted ports; prevents reception of fake IP addresses and reduces ARP attacks, improving security
- **IP Source Guard**
filters packets on a per-port basis, which prevents illegal packets from being forwarded
- **ARP attack protection**
protects against attacks that use a large number of ARP requests, using a host-specific, user-selectable threshold

Overview

Multicast support

- **Internet Group Management Protocol (IGMP)**
utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks; supports IGMPv1, v2, and v3
- **Protocol Independent Multicast (PIM)**
defines modes of multicasting to allow one-to-many and many-to-many transmission of information; PIM Dense Mode (DM), Sparse Mode (SM), and Source-Specific Mode (SSM) are supported

Warranty and support

- **1-year warranty**
advance hardware replacement with 10-calendar-day delivery (available in most countries)
- **Electronic and telephone support**
limited electronic and business-hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to: www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to: www.hp.com/networking/warrantysummary
- **Software releases**
to find software for your product, refer to: www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to: www.hp.com/networking/warrantysummary

Configuration

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

Switch Chassis

HP FF 7904 Switch Chassis	JG682A
<ul style="list-style-type: none">• Must select min 1 Power Supply• Must select min 1 Fan Tray• Must select Min 1 Ethernet Module• 2U - Height	

Modules

Ethernet Modules

JG682A - System (std 0 // max 4) User Selection (min 1 // max 4) per enclosure

HP FF 7900 12p 40GbE QSFP+ SA Mod	JG683A
<ul style="list-style-type: none">• min=0 \ max=12 QSFP+ Transceivers	See Configuration Note:1
HP FF 7900 12p 40GbE QSFP+ SA Mod	JG683A
<ul style="list-style-type: none">• min=0 \ max=12 QSFP+ Transceivers	See Configuration Note:1

Configuration Rules:

Note 1	The following 40G Transceivers install into this Module: (Use #0D1 or #B01 if switch is CTO)
	HP X140 40G QSFP+ LC LR4 SM XCVR JG661A
	HP X140 40G QSFP+ MPO SR4 XCVR JG325B
	HP X140 40G QSFP+ CSR4 300m XCVR JG709A
	HP X240 40G QSFP+ QSFP+ 1m DAC Cable JG326A
	HP X240 40G QSFP+ QSFP+ 3m DAC Cable JG327A
	HP X240 40G QSFP+ QSFP+ 5m DAC Cable JG328A
	HP X240 QSFP+ 4x10G SFP+ 1m DAC Cable JG329A
	HP X240 QSFP+ 4x10G SFP+ 3m DAC Cable JG330A
	HP X240 QSFP+ 4x10G SFP+ 5m DAC Cable JG331A

Transceivers

QSFP+ Transceivers

HP X140 40G QSFP+ LC LR4 SM XCVR	JG661A
HP X140 40G QSFP+ MPO SR4 XCVR	JG325B
HP X140 40G QSFP+ CSR4 300m XCVR	JG709A
HP X240 40G QSFP+ QSFP+ 1m DAC Cable	JG326A

Configuration

HP X240 40G QSFP+ QSFP+ 3m DAC Cable	JG327A
HP X240 40G QSFP+ QSFP+ 5m DAC Cable	JG328A
HP X240 QSFP+ 4x10G SFP+ 1m DAC Cable	JG329A
HP X240 QSFP+ 4x10G SFP+ 3m DAC Cable	JG330A
HP X240 QSFP+ 4x10G SFP+ 5m DAC Cable	JG331A

Internal Power Supplies

JG682A - System (std 0 // max 2) User Selection (min 1 // max 2)

HP FF 7900 1800w AC Frt(Prt)-Bck PSU	JG840A
<ul style="list-style-type: none">includes 1 x c15, 1800w	See Configuration Note:1
PDU Cable NA/MEX/TW/JP	JG840A#B2B
<ul style="list-style-type: none">C15 PDU Jumper Cord (NA/MEX/TW/JP)	
PDU Cable ROW	JG840A#B2C
<ul style="list-style-type: none">C15 PDU Jumper Cord (ROW)	
High Volt Switch to Wall Power Cord	JG840A#B2E
<ul style="list-style-type: none">NEMA L6-20P Cord (NA/MEX/JP/TW)	

Configuration Rules:

Note 1	Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) or #B2E. (See Localization Menu)
Remarks:	Drop down under power supply should offer the following options and results: Switch to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO) Switch to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO) High Volt Power Electrical Module to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)

Switch Enclosure Options

Fan Trays

JG682A - System (std 0 // max 2) User Selection (min 2 // max 2) per switch

HP FF 7904 Frt(Prt)-Bck(Pwr) Fan Tray	JG684A
	See Configuration Note:1
HP FF 7904 Bck(Pwr)-Frt(Prt) Fan Tray	JG839A
	See Configuration Note:1

Configuration Rules:



Configuration

Note 1 Fan Trays cannot be mixed in the same switch enclosure

Mounting Kit

HP X421 Chassis Universal Rck Mntg Kit

JC665A

[See Configuration Note:1](#)

Configuration Rules:

Note 1 This item is optional and used by customers to allow the chassis to slide in and out of the rack

Remarks: Default a quantity of 1 when Switch is selected.

Technical Specifications

HP FlexFabric 7904 Switch Chassis (JG682A)

I/O ports and slots	4 I/O module slots Supports a maximum of 48 40GbE ports	
Power supplies	4 I/O module slots Supports a maximum of 48 40GbE ports	
Fan tray	2 fan tray slots JG684A for Front to Back airflow	
Physical characteristics	Dimensions	17.32(w) x 28.35(d) x 3.47(h) in (44 x 72 x 8.81 cm) (2U height)
	Weight	50.04 lb (22.7 kg) shipping weight chassis only (no fan tray or power supplies)
	Full configuration weight	87.7 lb (39.78 kg)
Memory and processor	Management module	Quad Core MIPS64 @ 1.2 GHz, 1 GB flash, 8 GB DDR2 SDRAM
Mounting	Mounts in an EIA standard 19-inch rack or other equipment cabinet (hardware included); horizontal surface mounting only	
Performance	Throughput	2.3 Bpps (64-byte packets)
	Switching capacity	3.8 Tb/s
	Routing table size	32768 entries (IPv4)
	MAC address table size	131072 entries
Reliability	Availability	99.999%
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	10% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Altitude	up to 13,123 ft (4 km)
	Acoustic	Low-speed fan: 57.6 dB, High-speed fan: 73.3 dB
Electrical characteristics	AC Voltage	100 - 120 / 200 - 240 VAC
	Current	16/60 A
	Power output	1800 W
	Frequency	50/60 Hz
	Notes	Based on a common power supply of 1,800 W (AC)
Safety	UL 60950-1; CAN/CSA 22.2 No. 60950-1; IEC 60950-1; EN 60950-1; FDA 21 CFR Subchapter J; AS/NZS 60950-1; RoHS Compliance EN 50581	
Revise Series Specs (Web only)	4 I/O module slots 2.38 Bpps, maximum, depending on configuration 3.84 Tb/s, maximum, depending on configuration	
Emissions	VCCI Class A; EN 55022 Class A; CISPR 22 Class A; IEC/EN 61000-3-2; IEC/EN 61000-3-3; ICES-003 Class A; AS/NZS CISPR 22 Class A; FCC (CFR 47, Part 15) Class A; ETSI EN 300 386	
Immunity	Generic	EN 55024

Technical Specifications

Management	IMC - Intelligent Management Center; command-line interface; out-of-band management (serial RS-232C); SNMP Manager; Telnet; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB	
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
Standards and protocols (applies to all products in series)	BGP RFC 1771 BGPv4 RFC 1772 Application of the BGP RFC 1997 BGP Communities Attribute RFC 1998 PPP Gandalf FZA Compression Protocol RFC 2385 BGP Session Protection via TCP MD5 RFC 2439 BGP Route Flap Damping RFC 2796 BGP Route Reflection RFC 2858 BGP-4 Multi-Protocol Extensions RFC 2918 Route Refresh Capability RFC 3065 Autonomous System Confederations for BGP RFC 3392 Capabilities Advertisement with BGP-4 RFC 4271 A Border Gateway Protocol 4 (BGP-4) RFC 4272 BGP Security Vulnerabilities Analysis RFC 4273 Definitions of Managed Objects for BGP-4 RFC 4274 BGP-4 Protocol Analysis RFC 4275 BGP-4 MIB Implementation Survey RFC 4276 BGP-4 Implementation Report RFC 4277 Experience with the BGP-4 Protocol RFC 4360 BGP Extended Communities Attribute RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP) RFC 5291 Outbound Route Filtering Capability for BGP-4 RFC 5292 Address-Prefix-Based Outbound Route Filter for BGP-4	MIBs RFC 1156 (TCP/IP MIB) RFC 1157 A Simple Network Management Protocol (SNMP) RFC 1215 A Convention for Defining Traps for use with the SNMP RFC 1229 Interface MIB Extensions RFC 1493 Bridge MIB RFC 1573 SNMP MIB II RFC 1643 Ethernet MIB RFC 1657 BGP-4 MIB RFC 1724 RIPv2 MIB RFC 1907 SNMPv2 MIB RFC 2011 SNMPv2 MIB for IP RFC 2012 SNMPv2 MIB for TCP RFC 2013 SNMPv2 MIB for UDP RFC 2096 IP Forwarding Table MIB RFC 2233 Interface MIB RFC 2571 SNMP Framework MIB RFC 2572 SNMP-MPD MIB RFC 2573 SNMP-Notification MIB RFC 2573 SNMP-Target MIB RFC 2578 Structure of Management Information Version 2 (SMIv2) RFC 2580 Conformance Statements for SMIv2 RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2665 Ethernet-Like-MIB RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB RFC 2787 VRRP MIB RFC 2819 RMON MIB RFC 2925 Ping MIB RFC 2932IP (Multicast Routing MIB) RFC 2933 IGMP MIB RFC 2934 Protocol Independent Multicast MIB for IPv4 RFC 3414 SNMP-User based-SM MIB RFC 3415 SNMP-View based-ACM MIB RFC 3417 Simple Network Management Protocol (SNMP) over IEEE 802 Networks RFC 3418 MIB for SNMPv3 RFC 3595 Textual Conventions for IPv6 Flow Label RFC 3621 Power Ethernet MIB
	Denial of service protection Automatic filtering of well-known denial-of-service packets CPU DoS Protection Rate Limiting by ACLs	
	Device management RFC 1157 SNMPv1/v2c RFC 1305 NTPv3 RFC 1902 (SNMPv2) RFC 2579 (SMIv2 Text Conventions) RFC 2580 (SMIv2 Conformance) RFC 2819 (RMON groups Alarm, Event, History and Statistics only) HTTP, SSHv1, and Telnet Multiple Configuration Files	

Technical Specifications

Multiple Software Images
SSHv1/SSHv2 Secure Shell
Web UI

General protocols

IEEE 802.1ad Q-in-Q
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.1X PAE
IEEE 802.3ab 1000BASE-T
IEEE 802.3ac (VLAN Tagging Extension)
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3ae 10-Gigabit Ethernet
IEEE 802.3ah Ethernet in First Mile over Point to Point Fiber - EFMF
IEEE 802.3ba 40 and 100 Gigabit Ethernet Architecture
IEEE 802.3x Flow Control
IEEE 802.3z 1000BASE-X
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1027 Proxy ARP
RFC 1035 Domain Implementation and Specification
RFC 1042 IP Datagrams
RFC 1058 RIPv1
RFC 1142 OSI IS-IS Intra-domain Routing Protocol
RFC 1195 OSI ISIS for IP and Dual Environments
RFC 1213 Management Information Base for Network Management of TCP/IP-based internets
RFC 1293 Inverse Address Resolution Protocol
RFC 1305 NTPv3
RFC 1350 TFTP Protocol (revision 2)
RFC 1393 Traceroute Using an IP Option
RFC 1519 CIDR
RFC 1531 Dynamic Host Configuration Protocol
RFC 1533 DHCP Options and BOOTP Vendor Extensions
RFC 1591 DNS (client only)
RFC 1624 Incremental Internet Checksum

RFC 3813 MPLS LSR MIB
RFC 3814 MPLS FTN MIB
RFC 3815 MPLS LDP MIB
RFC 3826 AES for SNMP's USM MIB
RFC 4133 Entity MIB (Version 3)
RFC 4444 Management Information Base for Intermediate System to Intermediate System (IS-IS)

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
RFC 1155 Structure of Management Information
RFC 1157 SNMPv1
RFC 1448 Protocol Operations for version 2 of the Simple Network Management Protocol (SNMPv2)
RFC 2211 Controlled-Load Network
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
RFC 3176 sFlow
RFC 3411 SNMP Management Frameworks
RFC 3412 SNMPv3 Message Processing
RFC 3414 SNMPv3 User-based Security Model (USM)
RFC 3415 SNMPv3 View-based Access Control Model (VACM)
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)

OSPF

RFC 1245 OSPF protocol analysis
RFC 1246 Experience with OSPF
RFC 1765 OSPF Database Overflow
RFC 1850 OSPFv2 Management Information Base (MIB), traps
RFC 2154 OSPF w/ Digital Signatures (Password, MD-5)
RFC 2328 OSPFv2
RFC 2370 OSPF Opaque LSA Option
RFC 3101 OSPF NSSA
RFC 3137 OSPF Stub Router Advertisement
RFC 3623 Graceful OSPF Restart
RFC 3630 Traffic Engineering Extensions to OSPFv2
RFC 4061 Benchmarking Basic OSPF Single Router Control Plane Convergence
RFC 4062 OSPF Benchmarking Terminology and Concepts
RFC 4063 Considerations When Using Basic OSPF Convergence Benchmarks
RFC 4222 Prioritized Treatment of Specific OSPF Version 2 Packets and Congestion Avoidance
RFC 4577 OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)

Technical Specifications

RFC 1701 Generic Routing Encapsulation
RFC 1721 RIP-2 Analysis
RFC 1723 RIP v2
RFC 1812 IPv4 Routing
RFC 2082 RIP-2 MD5 Authentication
RFC 2091 Trigger RIP
RFC 2131 DHCP
RFC 2138 Remote Authentication Dial In User Service (RADIUS)
RFC 2236 IGMP Snooping
RFC 2338 VRRP
RFC 2453 RIPv2
RFC 2644 Directed Broadcast Control
RFC 2763 Dynamic Name-to-System ID mapping support
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2865 Remote Authentication Dial In User Service (RADIUS)
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
RFC 2973 IS-IS Mesh Groups
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3567 Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication
RFC 3719 Recommendations for Interoperable Networks using Intermediate System to Intermediate System (IS-IS)
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3787 Recommendations for Interoperable IP Networks using Intermediate System to Intermediate System (IS-IS)
RFC 3847 Restart signaling for IS-IS
RFC 4251 The Secure Shell (SSH) Protocol Architecture
RFC 4486 Subcodes for BGP Cease Notification Message
RFC 4884 Extended ICMP to Support Multi-Part Messages
RFC 4941 Privacy Extensions for Stateless Address Autoconfiguration in IPv6
RFC 5130 A Policy Control Mechanism in IS-IS Using Administrative Tags

IP multicast

RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode

RFC 4811 OSPF Out-of-Band LSDB Resynchronization
RFC 4812 OSPF Restart Signaling
RFC 4813 OSPF Link-Local Signaling
RFC 4940 IANA Considerations for OSPF

QoS/CoS

IEEE 802.1P (CoS)
RFC 1349 Type of Service in the Internet Protocol Suite
RFC 2211 Specification of the Controlled-Load Network Element Service
RFC 2212 Guaranteed Quality of Service
RFC 2474 DSCP DiffServ
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)

Security

IEEE 802.1X Port Based Network Access Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 1334 PPP Authentication Protocols (PAP)
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP)
RFC 2409 The Internet Key Exchange (IKE)
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 2868 RADIUS Attributes for Tunnel Protocol Support
RFC 2869 RADIUS Extensions
Access Control Lists (ACLs)
Guest VLAN for 802.1x
MAC Authentication
SSHv1/SSHv2 Secure Shell

Technical Specifications

RFC 3376 IGMPv3
RFC 3446 Anycast Rendezvous Point (RP)
mechanism using Protocol Independent Multicast
(PIM) and Multicast Source Discovery Protocol
(MSDP)
RFC 3973 PIM Dense Mode
RFC 4541 Considerations for Internet Group
Management Protocol (IGMP) and Multicast Listener
Discovery (MLD) Snooping Switches
RFC 4601 PIM Sparse Mode

Accessories

HP FlexFabric 7900 Switch Series accessories

Modules

HP FlexFabric 7900 12-port 40GbE QSFP+ SA Module JG683A

Transceivers

HP X140 40G QSFP+ LC LR4 SM 10km 1310nm Transceiver JG661A

HP X140 40G QSFP+ MPO MM 850nm CSR4 300m Transceiver JG709A

HP X140 40G QSFP+ MPO SR4 Transceiver JG325B

HP X240 40G QSFP+ to QSFP+ 1m Direct Attach Copper Cable JG326A

HP X240 40G QSFP+ to QSFP+ 3m Direct Attach Copper Cable JG327A

HP X240 40G QSFP+ to QSFP+ 5m Direct Attach Copper Cable JG328A

HP X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable JG329A

HP X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable JG330A

HP X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable JG331A

Power Supply

HP FlexFabric 7900 1800w AC Front (Port Side) to Back (Power Side) Airflow Power Supply Unit JG840A

Mounting Kit

HP X421 Chassis Universal 4-post Rack Mounting Kit JC665A

HP FlexFabric 7904 Switch Chassis (JG682A)

HP FlexFabric 7904 front (Port side) to back (Power side) airflow Fan Tray JG684A

To learn more, visit: www.hp.com/networking

© Copyright 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.